



RNAS 224-10S



ACME Portable's rugged network appliances are Gigabit Ethernet Layer 2 and Layer 3 access switches. They are built to be easy to deploy, manage, and troubleshoot.

Technical Specifications

PRODUCT	RNAS 224-10S
CPU	APM86392 600 MHZ DUAL CORE
MEMORY	512 MB
PORTS	24X 10/100/1000 (POE+) + 4X GIGABIT SFP
POWER SUPPLY	120/230 V, 50/60 HZ
WEIGHT	33 LBS (15 KG)
HUMIDITY	(OPERATING) 10 - 95% (NON-CONDENSING), (STORAGE) 10 - 95% (NON-CONDENSING)
TEMPERATURE	(OPERATING) 23 °F ~ 113 °F
STORAGE	(STORAGE) -13 °F ~ 158 °F

* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



Headquarters - USA

ACME Portable Machines, Inc.
1330 Mountain View Circle,
Azusa, CA, 91702, USA
Tel: +1 626.610.1888
Fax: +1 626.610.1881
www.acmeportable.com

Germany

ACME Portable Computer GmbH
Benzstraße 15,
76185 Karlsruhe, Germany
Tel: +49.721.570.4530
Fax: +49.721.570.45329
www.acmeportable.de

Taiwan

ACME Portable Corp.
5F, No 25, Wuquan 3rd Road,
Wugu Dist., New Taipei City 248,
Taiwan R.O.C
Tel: +886.2.2298.3636
Fax: +886.2.2298.3737
www.acmeportable.com.tw