YUAN

AIR6NO-C-MB NX

Business Card Size AI Edge Motherboard

Features

- · Powered by NVIDIA® Jetson Orin™ NX Super up to 157 / 117 TOPS
- · Business Card Size
- · 2×M.2 Gen 4×2 M Key / Gen 4×1 E Key
- · 1×USB3.2 Gen2
- · 1×Mini DisplayPort



Specifications

System							
SOM	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano			
SOIVI	16GB Super	8GB Super	8GB Super	4GB Super			
СРИ	8-Core Arm® Cortex®-A78AE v8.2	6-Core Arm® Cortex®-A78AE v8.2	6-Core Arm® Cortex®-A78AE v8.2 64-Bit CPU 1.5MB L2 + 4MB L3				
	64-Bit CPU 2MB L2 + 4MB L3	64-Bit CPU 1.5MB L2 + 4MB L3					
GPU	1024-Core NVIDIA Ampere Architecture GPU with 32 Tensor Cores		1024-core NVIDIA Ampere	512-core NVIDIA Ampere			
			Architecture GPU with 32 Tensor Cores	Architecture GPU			
Al Performance	157 TOPS	117 TOPS	67 TOPS	with 16 Tensor Cores 34 TOPS			
System Memory	16GB 128-bit LPDDR5	8GB 128-bit LPDDR5	8GB 128-bit LPDDR5	4GB 64-bit LPDDR5			
	102.4GB/s	102.4GB/s	102 GB/s	51 GB/s			
Interface	·	,	<u>, </u>				
Storage	Supports External NVMe						
Display Interface	1×Mini DP1.4						
Ethernet	1×RJ45 for 10/100/1000Mbps Ethernet (DHCP Client)						
	1×M.2 2230 M Key PCle Gen4×2 Slot (Nano: Gen3×2)						
Expansion Slot	1×M.2 2230 E Key PCle Gen4×1 Slot (Nano: Gen3×1)						
USB	1×USB3.2 Gen2 (Type-C)						
MIPI	8 MIPI CSI-2 Lanes (D-PHY 2.1, Support MIPI Camera, Capture Card)						
Peripheral Communication	Custom Connector 2×USB3.2 Gen2 1×PCle Gen4×4 4×GPIO 2×UART (UARTO(*), UART1) 3×I2C 1×CAN Bus 10 Pin Header 1×USB2.0 4×GPIO 1×I2C 6 Pin Wafer 1×UART (*) 4 Pin Header 5V / 3A						
Misc. Features	* Please select either Custom Connector UART or 6 Pin Wafer UART to use Firmware Upgradable						
Development Environment	1						
JetPack	6.2 or Higher						
Environment							
Power Supply	DC input: 12~36V						
Power Consumption	ТВА						
Operating Temperature	0~60 C with Airflow						
Storage Temperature	-20~80 °C						
Certification	CE, FCC						

SDK / Software

Video Feature					
SOM	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ NX	NVIDIA Jetson Orin™ Nano	NVIDIA Jetson Orin™ Nano	
30101	16GB Super	8GB Super	8GB Super	4GB Super	
Video Encode	AV1 (UHP)				
	1×4K60 3×4K30 6×1080p60 12×1080p30		1080p30 supported by 1-2 CPU cores		
	H.265 (UHP)				
	1×4K60 3×4K30 6×1080p60 12×1080p30				
	H.264 (UHP)				
	1×4K60 2×4K30 5×1080p60 11×1080p30				
Video Decode	AV1 (Main Profile)		AV1 (Main Profile) 1×4K60 2×4K30 5×1080p60 10×1080p30		
	1×8K30 2×4K60 4×4K30 10×1080p60 20×1080p30			H.265 (Main, Main10)	
	H.265 (Main, Main10)		, , ,	1×4K60 2×4K30 5×1080p60 11×1080p30	
	1×8K30 2×4K60 4×4K30 9×1080p60 18×1080p30 H.264 (Baseline, Main, High)		H.264 (Baseline, Main, High)		
	1×4K60 2×4K30 5×1080p60 11×1080p30		, , , , , ,	1×4K30 3×1080p60 7×1080p30	
	VP9 (Profile 0, Profile 2) VP9 (Profile 2)		μ30		
	1×4K60 3×4K30 7×1080p60 15×1080p30			1×4K60 2×4K30 5×1080p60 10×1080p30	
SDK	1 TV4KOO 2V4KOO 1V4TOOOhoo 17V4TOOOhoo 1V4KOO 2V4KOO 1V4TOOOhoo 10V4TOOOhoo				
July	Capture				
	High Performance Renderer				
	Image Snapshot				
	De-interlace, Alpha Blending Engine				
	Auto Signal Detection				
	2D/3D Video, Audio and VANC Streams Capture				
	Record				
	Encrypt / Sync / Clone / Recording				
QCAP	Time-Shifting / Rewind / Pre-Event / Recording				
	Multi-Streams (3D) Recording				
	Animation Transition Effect				
	Video Cropping, Scaling and Alpha Blending Engine				
	Stream				
	2D/3D Universal Stream Client				
	2D/3D Multi-Streams Stream Server				
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)				
	Animation Transition Effect				
	Video Cropping, Scaling and Alpha Blending Engine				
	*Separate License Required ALSDV Intervented Multiple Algorithms and Dean Learning Models in Verious Fields of Applications				
QDEEP	AI SDK Integrated Multiple Algorithms and Deep-Learning Models in Various Fields of Applications				
	Face Recognition Objects Detection				
	Objects Detection Objects Segment				
QDLLI	Optical Character Recognition				
	License Plate Recognition				
	Customizable Video Al Functions Upon Request				
Software (Optional)		<u> </u>			
Xtreamer	Web Based User Interface		Toward Tolkshoot	The state of the s	
	Encode / Decode			- Company Comp	
	AV1, H.26X				
	Color Format Adjust				
	444 / 422 / 420, 10Bit / 8Bit Select				
	Record				
	MP4, TS			or Carlos	
				The state of the s	
	RTSP, RTMP, HLS, SRT, TS, WebRTC. NDI-HX (*), Full NDI (*)				
	*Separate License Required				
		C. NDI-HX (*), Full NDI (*)	tenant and	Name	

Mechanical

· Dimension: 90mm × 55mm

 \cdot Weight: 130g (With SOM and Fan)

- $\mbox{\ensuremath{^{\bullet}}}$ All registered trademarks are the property of their owners. The photo is for reference only.
- * Technology License Patent Royalty. Supplier (YUAN Technology Ltd.) as an OEM vendor is not responsible for any royalties applied to the Models and collected by any patent or trade mark holders or his exclusive, non-exclusive.

Licensees or representatives such as MPEGLA, Dolby, Thomson, Sisvel, H.264, MPEG4 and any other natural or legal person. All concerning royalties of patents and trade marks will be paid or negotiated with the above mentioned owner by you. In case of any patent or trademark infringement you are responsible for all necessary processes and costs. You accept and acknowledge that all prices of Models offered by supplier are exclusive of any royalties, charges or license fees for any patents in any countries or areas.