



# RNAS 448-10S



ACME Portable's rugged network appliances are Gigabit Ethernet Layer 2 and Layer 3 access switches. They are built to be easy to deploy, manage, and troubleshoot.

# Technical Specifications

PRODUCT	RNAS 448-10S
CPU	APM86392 600 MHZ DUAL CORE
MEMORY	512 MB
PORTS	48X 10/100/1000 (POE+) + 4X GIGABIT SFP
POWER SUPPLY	120/230 V, 50/60 HZ
WEIGHT	44.1 LBS (20 KG)
HUMIDITY	(OPERATING) 10 - 95% (NON-CONDENSING), (STORAGE) 10 - 95% (NON-CONDENSING)
TEMPERATURE	(OPERATING) 23 °F ~ 113 °F
STORAGE	(STORAGE) -13 °F ~ 158 °F

\* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



## Headquarters - USA

ACME Portable Machines, Inc.  
1330 Mountain View Circle,  
Azusa, CA, 91702, USA  
Tel: +1 626.610.1888  
Fax: +1 626.610.1881  
[www.acmeportable.com](http://www.acmeportable.com)

## Germany

ACME Portable Computer GmbH  
Benzstraße 15,  
76185 Karlsruhe, Germany  
Tel: +49.721.570.4530  
Fax: +49.721.570.45329  
[www.acmeportable.de](http://www.acmeportable.de)

## Taiwan

ACME Portable Corp.  
5F, No 25, Wuquan 3rd Road,  
Wugu Dist., New Taipei City 248,  
Taiwan R.O.C  
Tel: +886.2.2298.3636  
Fax: +886.2.2298.3737  
[www.acmeportable.com.tw](http://www.acmeportable.com.tw)